

MATERIAL SAFETY DATA SHEET
Emergency Phone: Chemtrec 800-424-9300

1. Product Identification

Product Name: 0485-Syseal® Tape

Description: A solventless pressure sensitive adhesive bonding tape based on a blend of synthetic hot melt rubber and resin.

2. Hazardous Ingredients

None. Hazard warning not required.

3. Physical-Chemical Characteristics

Appearance: Amber-colored tape
Boiling Point: Not available
Melting Point: Not available
Odor: Slight
Solubility in Water: Insoluble
Soluble in: Aromatic and aliphatic hydrocarbons
Specific Gravity: 0.98 g/cm³
Working Temperatures 32°F – 105°F
Total Thickness: 16 mils (.400mm)

4. Fire and Explosion Hazard Data

Flash Point: Not available.
Extinguishing Media: No restriction.
Special Fire Fighting Procedures: No special equipment required.

5. Stability and Reactivity

Thermal Decomposition: Above 200°C
Hazardous Reactions: No hazardous reactions observed.

6. Health Hazard Data

Health Hazards:
Toxicological Information: There are no known toxic hazards.
Ecological Information: No known hazards.
Exposure Controls/Personal Protection-
No special measures required.
Emergency and First Aid Procedures-
No special measures required.

7. Precautions for Safe Handling and Use

Accidental Release Measure: Take up mechanically.
Disposal Considerations: Incineration or landfill in accordance with local regulations. Packaging materials should be treated as household waste or as recycling material.
Handling and Storage: Store in a cool, dry place.

9. Transport Information

UN No: None RID/ADR Class: None IMO Class: None
ICAO Class: None Symbols: None

10. Regulatory Information

No labeling is required for this material under EEC regulations.

11. Other Information

The data given here is based on current knowledge and experience. It should not be construed as guaranteeing specific properties.